

SAFETY DATA SHEETS

Euroflex Series

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

- Product name:**
- Euroflex Cleaner - page 2
 - Euroflex Bio-wash – page 7
 - Euroflex Clearseal – page 13
 - Euroflex Primer – page 17
 - Euroflex High Performance Roof Waterproofer – page 22
 - Roofing and Joint Sealant – page 27
 - Tar and Bitumen Isolator – page 33
 - One Component Coatings and Adhesives - page 37

Company name: Interflex Limited
Unit7A
Crifin Enterprise Centre
Oxton Road
Epperstone
Nottinghamshire
NG14 6AT

Tel: 0115 9129 749
Fax: 0115 9129 749
Mobile: 07802551757
Email: enquiries@interflex.org.uk

SAFETY DATA SHEET

Euroflex Series

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

Product name: Euroflex Cleaner

Company name: Interflex Limited
Unit7A
Criftin Enterprise Centre
Oxton Road
Epperstone
Nottinghamshire
NG14 6AT

Tel: 0115 9129 749
Fax: 0115 9129 749
Email: enquiries@interflex.org.uk

2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components: Xylene 1-10%
1330-20-7
Xn; R20/21-38

1,2,4 – Trimethylbenzene 50-60%
95-63-6
Xn; R20 Xi; R36 Xi; R37 Xi; R38 N; R51/53

Solent Naphtha (Petroleum), Light aromatic 30-40%
64742-95-6
Xn: R65

3. HAZARDS IDENTIFICATION

Main hazards: Flammable. Harmful by inhalation. Irritating to eyes, respiratory system and skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed.

4. FIRST AID MEASURES

Skin contact:	Wash off immediately with soap and plenty of water, removing all contaminated clothes and shoes.
Eye contact:	In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Inhalation:	Move to fresh air. Consult a physician after significant exposure.
Ingestion:	Do not induce vomiting without medical advice. Drink plenty of water. Obtain medical attention.
General advice:	If you feel unwell, seek medical advice (show the label where possible). Keep warm and in a quiet place. Take off contaminated clothing and shoes immediately. Wash contaminated clothing before re-use.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:	Use of extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Specific hazards:	In the event of fire black smoke may be formed.
Special protective equipment for fire fighters:	In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:	Ensure adequate ventilation. Keep people away from the upwind or spill/leak.
Environmental precautions:	Do not allow material to contaminate ground water system. Prevent product from entering drains.
Methods for cleaning up:	Soak up with inert absorbent material and dispose of as hazardous waste. Small amounts: Evaporates.

7. HANDLING AND STORAGE

Handling:	Wear personal protective equipment. Do not breathe vapours or spray mist. Use only in well-ventilated areas.
Storage:	Keep container tightly closed in a dry and well-ventilated place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit(s):	Xylene TWA(ppm):50 TWA(mg/m ³):220 STEL(ppm):100 STEL(mg/m ³):441
Engineering measures to reduce exposure:	Ensure adequate ventilation, especially in confined areas.
Respiratory protection:	In case of insufficient ventilation wear suitable respiratory equipment. In the case of hazardous fumes, wear self-contained breathing apparatus.
Hand protection:	PVC or other plastic material gloves.
Eye protection:	Tightly fitting safety goggles. Avoid contact with eyes.
Skin and body protection:	Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice, rubber or plastic apron rubber or plastic boots.

9. PHYSICAL AND CHEMICAL PROPERTIES

Description:	Liquid.
Odour:	Characteristic aromatic.
Flash point:	41°C.
Water solubility:	Immiscible.

10. STABILITY AND REACTIVITY

Stability:	Stable at normal conditions.
Conditions to avoid:	Heat, flames and sparks.
Materials to avoid:	Oxidising agents.
Hazardous decomposition products:	None under normal use.

11. TOXICOLOGICAL INFORMATION

Acute toxicity:	Harmful if swallowed.
Primary irritation:	Contact with eyes or skin causes irritation.
Repeated or prolonged exposure:	Prolonged exposure causes local irritation of skin and mucous membranes, especially to the eyes.

12. ECOLOGICAL INFORMATION

Ectotoxicity: Toxicity to fish. May cause long-term adverse effects in the aquatic environment.

13. DISPOSAL CONSIDERATIONS

General information: Can be incinerated, when in compliance with local regulations.
Dispose of in accordance with local regulations.

Contaminated packaging: Fully drained containers, which are drop-and scrape-free, can be treated as industrial waste, and can possibly be recycled.

14. TRANSPORT INFORMATION

ADR/RID

UN No.:	1268	Class:	3
Hazard ID:	30	Proper Shipping:	Petroleum Distillates
Packing group:	III	Name:	N.O.S.

IMO

UN No.:	1268	Class:	3
Marine pollutant:		EmS:	F-E-S-E-
Packing group:	III		

IATA/DGR

UN No.:	1268	Class:	3
Packaging:	310	Packing group:	III

15. REGULATORY INFORMATION

Labelling: The product is classified and labelled in accordance with EC directives or respective national laws.

Symbol(s) Xn; N;



R – phrase(s): R10 – Flammable.
R20 – Harmful by inhalation.
R36/37/38 – Irritating to eyes, respiratory system and skin.
R42/43 – May cause sensitisation by inhalation and skin contact.
R51/53 – Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65 – Harmful: may cause lung damage if swallowed.

S – phrase(s): S61 – Avoid release to the environment. Refer to special instructions/safety data sheets.

16. OTHER INFORMATION

Text of R phrases mentioned in section 2:	R20/21 – Harmful by inhalation and in contact with skin. R38 – Irritating to skin. R20 – Harmful by inhalation. R36 – Irritating to eyes. R37 – Irritating to respiratory system. R51/53 – Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 – Harmful: may cause lung damage if swallowed.
Recommended restrictions:	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication.

SAFETY DATA SHEET

Euroflex Series

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

Product name: Euroflex Bio-Wash

Company name: Interflex Limited
Unit 7A
Crifin Enterprise Centre
Oxton Road
Epperstone
Nottinghamshire
NG14 6AT

Tel: 0115 9129 749

Fax: 0115 9129 749

Email: t.makar@ntlworld.com

Web: www.interflex.org.uk - email: enquiries@interflex.org.uk

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients: Coco Alkyl Dimethylbenzyl Ammonium Chlorine 1-10%
Cas: 61789-71-7
Einecs: 263-080-8
[Xn] R21/22; [C] R34; [N] R50

3. HAZARDS IDENTIFICATION

Main hazards: Irritating to eyes and skin.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There maybe irritation and redness at the site of contact.

Eye contact: There maybe pain and redness. The eyes may water profusely. There maybe severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There maybe soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There maybe irritation of the throat with a feeling of tightness in the chest.

(cont....)

Euroflex Bio-Wash

4. FIRST AID MEASURES (ACTION)

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.
- Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist contamination.
- Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so.

5. FIRE-FIGHTING MEASURES

- Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.
- Exposure hazards:** In combustion emits toxic fumes.
- Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions:** Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing – see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.
- Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.
- Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

- Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.
- Storage conditions:** Store in cool, well-ventilated area. Keep container tightly closed.

SAFETY DATA SHEET

Euroflex Bio-Wash

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering measures:	Ensure there is sufficient ventilation of the area.
Respiratory protection:	Self-contained breathing apparatus must be available in case of emergency.
Hand protection:	Protective gloves.
Eye protection:	Tightly fitting safety goggles. Ensure eye bath is to hand.
Skin protection:	Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State:	Liquid.
Colour:	Colourless.
Odour:	Barely perceptible odour.
Evaporation rate:	Negligible.
Solubility in water:	Miscible in all proportions.
Viscosity:	Non-viscous.
Relative density:	0.99

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to avoid:	Heat.
Materials to avoid:	Strong oxidising agents. Strong acids.
Hazardous decomposition products:	In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Routes of exposure:	Refer to section 4 of SDS for routes of exposure and corresponding symptoms.
----------------------------	--

(cont....)

SAFETY DATA SHEET

Euroflex Bio-Wash

12. ECOLOGICAL INFORMATION

Mobility:	Readily absorbed into soil.
Persistence and degradability:	No data available.
Bioaccumulative potential:	No data available.
Other adverse effects:	Toxic to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

NB:	The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.
------------	---

14. TRANSPORT INFORMATION

ADR/RID

UN No.:	--
Hazard ID:	"Not Subject to ADR"

IMDG/IMO

UN No.:	--
----------------	----

IATA/ICAO

UN No.:	--
----------------	----

15. REGULATORY INFORMATION

Hazard symbols:	Irritant.
------------------------	-----------



R – phrase(s):	R36/38 – Irritating to eyes and skin.
-----------------------	---------------------------------------

S – phrase(s):	FOR USE ONLY AS A SURFACE BIOCIDES. S36/37/39 – Wear suitable protective clothing, gloves and eye/face protection. Contains 2-phenyl phenol 0.25% w/w (2.5g/l) and Benzalkonium chloride 0.99% w.w (9.9g/l). This product is approved under the control of pesticides regulations 1986 for use as directed. HSE 7183 WASH SPLASHES from skin and hands immediately.
-----------------------	--

(cont....)

15. REGULATORY INFORMATION (continued)

- S – phrase(s):** WASH HANDS AND EXPOSED SKIN before meals and after use.
KEEP IN ORIGINAL CONTAINER, tightly closed in a safe place.
S13 – Keep away from food, drink and animal feeding stuffs.
S2 – Keep out of the reach of children.
S46 – If swallowed, seek medical advice immediately and show this container or label.
FOR USE ONLY AS A SURFACE BIOCIDES.
APPLY 1 LITRE OF PRODUCT PER 5-10-SQUARE METRES OF SURFACE
DEPENDING ON POROSITY OF THE SUBSTRATE.
WEAR SUITABLE PROTECTIVE CLOTHING, COVERALLS, AND SYNTHETIC RUBBER/PVC GLOVES when using.
DO NOT BREATHE SPRAY MIST. Otherwise wear respiratory protective equipment and eye protection (see HSE Guidance booklet HSE (G) 53: “respiratory protective equipment – a practical guide for users”).
DO NOT CONTAMINATE FOODSTUFFS, EATING UTENSILS OR FOOD CONTACT SURFACES.
COVER WATER STORAGE TANKS before application.
THIS MATERIAL AND CONTAINER must be disposed of in a safe way.
WHEN USING, DO NOT EAT, DRINK OR SMOKE.
UNPROTECTED PERSONS AND ANIMALS SHOULD BE KEPT AWAY FROM TREATED AREAS FOR 48 HOURS OR UNTIL SURFACES ARE DRY.
PREVENT ANY SURFACE RUN OFF FROM ENTERING DRAINS.
- Precautionary phases:** DANGEROUS TO FISH AND OTHER AQUATIC LIFE.
REMOVE OR COVER FISH TANKS AND BOWLS before application.
AVOID ALL CONTACT WITH PLANT LIFE.
DO NOT CONTAMINATE watercourses.
READ ALL PRECAUTIONS BEFORE USE. HSE 7183.
WASH SPLASHES from skin and hands immediately.
WASH HANDS AND EXPOSED SKIN before meals and after use.
KEEP IN ORIGINAL CONTAINER, tightly closed in a safe place.
- Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user’s attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

(cont....)

16. OTHER INFORMATION

Risk phrases used in section 2: R21/22 – Harmful in contact with skin and if swallowed.
R34 – Causes burns.
R50 – Very toxic to aquatic organisms.

Legal disclaimer: The above information is believed to be correct but does not purport to be all-inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

SAFETY DATA SHEET

Euroflex Clearseal

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product name: Euroflex Clearseal.

Product code:

Use/description of product: Waterproofing Product

Company name: Interflex Limited
Unit 7A
Crifftin Enterprise Centre
Oxton Road
Epperstone
Nottinghamshire
NG14 6AT

Tel: 0115 9129 749
Fax: 0115 9129 749
Email: t.makar@ntlworld.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Contains: Polysiloxane emulsion in water.

3. HAZARDS IDENTIFICATION

Main hazards: No significant hazard.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There maybe mild irritation at the site of contact.

Eye contact: There maybe irritation and redness.

Ingestion: There maybe irritation of the throat.

Inhalation: No symptoms.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

(cont....)

5. FIRE-FIGHTING MEASURES

- Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.
- Exposure hazards:** In combustion emits toxic fumes.
- Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions:** Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid.
- Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.
- Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

- Handling requirements:** Avoid direct contact with the substance.
- Storage conditions:** Store in cool, well-ventilated area. Keep container tightly closed. Store in original containers between 5° and 25°C. Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties.
- Suitable packaging:** Must only be kept in original packaging.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Respiratory protection:** Respiratory protection not required.
- Hand protection:** Protective gloves.
- Eye protection:** Safety glasses. Ensure eye bath is to hand.
- Skin protection:** Protective clothing.

(cont....)

SAFETY DATA SHEET

Clearseal

9. PHYSICAL AND CHEMICAL PROPERTIES

State:	Liquid.
Colour:	White.
Odour:	Barely perceptible odour.
Evaporation rate:	Slow.
Solubility in water:	Miscible in all proportions.
Viscosity:	Non-viscous.
Boiling point/range °C:	100
Flash point °C:	100
Relative density:	0.97
pH:	4-5

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to avoid:	Heat.
Materials to avoid:	Strong oxidising agents. Strong acids.
Hazardous decomposition products:	In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Routes of exposure:	Refer to section 4 of SDS for routes of exposure and corresponding symptoms.
----------------------------	--

12. ECOLOGICAL INFORMATION

Mobility:	Readily absorbed into soil.
Persistence and degradability:	Biodegradable.
Bioaccumulative potential:	No bioaccumulation potential.
Other adverse effects:	Negligible ecotoxicity.

(cont....)

SAFETY DATA SHEET

Clearseal

13. DISPOSAL CONSIDERATIONS

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR/RID

UN No.: --
Hazard ID: "Not Subject to ADR"

IMDG/IMO

UN No.: --

IATA/ICAO

UN No.: --

15. REGULATORY INFORMATION

Hazard symbols: No significant hazard.

Note: The regulatory information given above only indicates the principal regulations these specifically applicable to the product described in the safety data sheet. The users attention is drawn to the possible existence of additional provisions which complete regulations. Refer to all applicable national, international and local regulations or provisions.

16. ADDITIONAL INFORMATION

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

SAFETY DATA SHEET

Euroflex Series

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

Product name: Euroflex Primer

Company name: Interflex Limited
Unit 7A
Criftin Enterprise Centre
Oxton Road
Epperstone
Nottinghamshire
NG14 6AT

Tel: 0115 9129 749
Fax: 0115 9129 749
Email: t.makar@ntlworld.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components: Xylene 1-10%
1330-20-7
Xn: R20/21-38

1, 2, 4 – Trimethylbenzene 20-30%
95-63-6
Xn: R20 Xi, R36 Xi, R37 Xi, R38 N, R51/53

Solvent Naphtha (Petroleum), Light aromatic 10-20%
64742-95-6
Xn; R65

Methylenediphenyl diisocyanate 10-20%
26447-40-5
Xn; R20-R36/37/38-42/43

3. HAZARDS IDENTIFICATION

Main hazards: Flammable. Harmful by inhalation. Irritating to eyes, respiratory system and skin. May cause sensitisation by inhalation and skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed.

(cont....)

Euroflex Primer

4. FIRST AID MEASURES

Skin contact:	Wash off immediately with soap and plenty of water, removing all contaminated clothes and shoes.
Eye contact:	In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Inhalation:	Move to fresh air. Consult a physician after significant exposure.
Ingestion:	Do not induce vomiting without medical advice. Drink plenty of water. Obtain attention.
General advice:	If you feel unwell, seek medical advice (show the label where possible). Keep warm and in a quiet place. Take off contaminated clothing and shoes immediately. Wash contaminated clothing before re-use.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Specific hazards:	In the event of fire black smoke may be formed.
Special protective equipment for fire fighters:	In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:	Ensure adequate ventilation. Keep people away from the upwind of spill/leak.
Environmental precautions:	Do not allow material to contaminate ground water system. Prevent product from entering drains.
Methods for cleaning up:	Soak up with inert absorbent material and dispose of as hazardous waste. Small amounts: Evaporates.

7. HANDLING AND STORAGE

Handling:	Wear personal protective equipment. Do not breathe vapours or spray mist. Use only in well-ventilated areas.
Storage:	Keep container tightly closed in a dry and well-ventilated place.

SAFETY DATA SHEET

Euroflex Primer

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit(s):	Xylene TWA(ppm):50 TWA(mg/m ³):220 STEL(ppm):100 STEL(mg/m ³):441
Engineering measures to reduce exposure:	Ensure adequate ventilation, especially in confined areas.
Respiratory protection:	In case of sufficient ventilation wear suitable respiratory equipment. In the case of hazardous fumes, wear self-contained breathing apparatus.
Hand protection:	PVC or other plastic material gloves.
Eye protection:	Tightly fitting safety goggles. Avoid contact with eyes.
Skin and body protection:	Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice, rubber or plastic apron, rubber or plastic boots.

9. PHYSICAL AND CHEMICAL PROPERTIES

Description:	Liquid.
Colour:	Brown.
Odour:	Characteristic aromatic.
Flash point:	41°C.
Water solubility:	Immiscible.

10. STABILITY AND REACTIVITY

Stability:	Stable at normal conditions.
Conditions to avoid:	Heat, fumes and sparks.
Materials to avoid:	Oxidising agents.
Hazardous decomposition products:	None under normal use.

(cont....)

SAFETY DATA SHEET

Euroflex Primer

11. TOXICOLOGICAL INFORMATION

Acute toxicity:	Harmful if swallowed.
Primary irritation:	Contact with eyes or skin causes irritation.
Repeated or prolonged exposure:	Prolonged exposure causes local irritation of skin and mucous membranes, especially to the eyes.

12. ECOLOGICAL INFORMATION

Ectotoxicity:	Toxicity to fish. May cause long-term adverse effects in the aquatic environment.
----------------------	---

13. DISPOSAL CONSIDERATIONS

General information:	Dispose of in accordance with local regulations.
-----------------------------	--

14. TRANSPORT INFORMATION

ADR/RID

UN No.: 1268	Class: 3
Hazard ID: 33	Proper Shipping Name: Petroleum Distillates
	N.O.S.

IMO

UN No.: 1268	Class: 3
Marine pollutant:	EmS: F-E-S-E-

IATA/DGR

UN No.: 1268	Class: 3
Packaging: 303	

(cont....)

15. REGULATORY INFORMATION

Labelling: The product is classified and labelled in accordance with EC directives or respective national laws.
P3 contains isocyanates. See information supplied by the manufacturer.

Symbol(s)  
Xn;N;

R – phrase(s): R10 – Flammable.
R20 – Harmful by inhalation.
R36/37/38 – Irritating to eyes, respiratory system and skin.
R42/43 – May cause sensitisation by inhalation and skin contact.
R51/53 – Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65 – Harmful: may cause lung damage if swallowed.

S – phrase(s): S23 – Do not breathe gas/fumes/vapour/spray.
S24 – Avoid contact with skin.
S37 – Wear suitable gloves.
S61 – Avoid release to the environment. Refer to special instructions/safety data sheets.
S63 – In case of accident by inhalation; remove casualty to fresh air and keep at rest.

16. OTHER INFORMATION

Text of R phrase mentioned in section 2: R20/21 – Harmful by inhalation and in contact with skin.
R38 – Irritating to skin.
R20 – Harmful by inhalation.
R36 – Irritating to eyes.
R37 – Irritating to respiratory system.
R51-53 – Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65 – Harmful: may cause lung damage if swallowed.
R36/37/38 – Irritating to eyes, respiratory system and skin.
R42/43 – May cause sensitisation by inhalation and skin contact.

Recommended restrictions: The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication.

SAFETY DATA SHEET

Euroflex Series

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

Product name: Euroflex High Performance Roof Waterproofer

Company name: Interflex Structural Waterproofing Systems Limited
Unit 7A,
Crifftin Enterprise Centre
Oxton Road
Epperstone
Nottinghamshire
NG14 6AT

Tel: 0115 9129 749
Fax: 0115 9129 749
Email: t.makar@ntlworld.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients:

	Conc.	CAS	EINECS	Symbols/Risk phrases
Methylenediphenyl diisocyanate	1-10%	26447-40-5	247-714-0	Xn; R20 Xi; R36/37/38 R/42/43
Diphenyl methane diisocyanate, isomers And homologues	0.5-1%	9016-87-9		Xn; R20-42/43 Xi; R36/37/38

3. HAZARDS IDENTIFICATION

Main hazards: May cause sensitisation by inhalation and skin contact.

4. FIRST AID MEASURES

Skin contact: Remove contaminated clothing. In the absence of Alcohol Impregnated Hand Wipes use plenty of soap and water, preferably soap developed to remove adhesive and paint. May cause sensitisation by skin contact. Seek medical attention if irritation or symptoms persist.

Eye contact: Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention.

Inhalation: Move the exposed person to fresh air. Seek medical attention. If breathing stops, provide artificial respiration. If breathing is difficult give oxygen.

Continued/.....

Ingestion: Wash out mouth with water. Do not induce vomiting. If swallowed, seek medical advice immediately and show this container or label. Never give anything by mouth to an unconscious person.

General information: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Keep the affected person warm and at rest. Remove contaminated clothing. Wash all contaminated clothing before reuse.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide (CO²) Dry chemical. Foam. Use as appropriate.

Fire hazards: Burning produces irritating, toxic and obnoxious fumes. Fire will produce dense black smoke.

Protective equipment Wear self contained breathing apparatus and protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Ensure adequate ventilation of the working area. Keep personnel away from spill. Evacuate personnel to a safe area.

Environmental precautions: Do not allow product to enter drains.

Methods for cleaning up: Remove mechanically, cover the remainder with an inert absorbent material eg sand, sawdust, vermiculite or other chemical absorbing material. After approximately 1 hour transfer the absorbent to a waste container, recover the spillage area if some of the spill remains, repeating until the area is clear. Transfer to suitable, labelled containers for disposal.

7. HANDLING AND STORAGE

Handling: Do not breathe gas/fumes/vapour/spray. Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. In all areas where MDI aerosols and /or vapour concentrations are produced, exhaust ventilation must be provided in such a way that the WEL is not exceeded. The air should be drawn away from the personnel handling the product. Respiratory protection is required in insufficiently ventilated working areas. An air fed mask, or for short periods of work, a combination of charcoal filter and particulate filter is recommended.

Storage: Further information on storage conditions, which must be observed to preserve quality, can be found in our product information sheet. Keep containers tightly closed. Keep in a cool, dry, well ventilated area.

Continued/.....

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limits

Diphenyl methane diisocyanate, isomers and homologues	WEL 8-hr limit ppm:	WEL 8-hr limit mg/m ³ : 0.02
	WEL 15 min limit ppm:	WEL 15 min limit mg/m ³ : 0.07

Engineering measures

Ensure adequate ventilation of the working area.

Occupational exposure controls:

Keep away from food, drink and animal feeding stuffs.

Respiratory protection:

Respiratory protection is required in insufficiently ventilated working areas. An air-fed mask, or for short periods of work, a combination of charcoal filter and particulate filter is recommended. Suitable half mask respirator with filter P3 (EN 141A1/A2) In case of hypersensitivity of the respiratory tract (e.g. asthmatics and those who suffer from chronic bronchitis) it is inadvisable to work with the product.

Hand protection:

To prevent product from coming into contact with hands chemical resistant rubber gloves must be worn. Butyl Rubber IIR (☐) Fluorinated rubber – FKM (☐) Nitrile rubber – NBR (☐) Polychloroprene – CR (☐) Polyvinyl Chloride – PVC (☐) Wash hands after handling the product.

Eye protection:

Avoid contact with eyes. In case of splashing, wear: Approved safety goggles.

Protective equipment:

Any areas of the body that could come into contact with the product, during normal application of the product or through accidental exposure, should be protected. Experience shows that the arms, face and head can be susceptible to contact due to the nature of applying the product. Assess the particular work activity and the area in which it is taking place to determine if further prevention of contact with the product is required. Overalls, hat/hoods and face shields may need consideration. Adopt best Manual Handling considerations when handling, carrying and dispensing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Description:	Viscous liquid.
Colour:	Grey.
Odour:	Mild.
Boiling point:	>200°C
Flash point:	>120°C
Relative density:	1.41
Water solubility:	Insoluble in water.

Continued/.....

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to avoid:	Direct sunlight. Do NOT allow to freeze. Heat. Moisture.
Materials to avoid:	Alcohols. Amines. Ammonia. Keep away from water. Oxidising agents. Will not decompose if stored and used as recommended.
Hazardous decomposition products:	No hazardous decomposition products when stored and handled correctly.
Hazardous reactions:	Exothermic reaction with amines and alcohols: reacts with water forming carbon dioxide gas: in closed containers, risk of bursting due to increase of pressure.

11. TOXICOLOGICAL INFORMATION

Acute toxicity:	Over exposure, especially when spraying coatings containing isocyanate without the necessary precautions, entails the risk of concentration dependent irritating effects on eyes, nose, throat and respiratory tract. Delayed appearance of the complaints and development of hypersensitivity (difficult breathing, coughing, asthma) are possible. Hypersensitive persons may suffer from these effects even at low isocyanate concentrations, including concentrations below the UK Workplace Exposure Limit (WEL).
Sensitisation:	May cause sensitisation by inhalation and skin contact.

12. ECOLOGICAL INFORMATION

Ecotoxicity:	No data is available on this product.
---------------------	---------------------------------------

13. DISPOSAL CONSIDERATIONS

General information:	Dispose of in compliance with all []. Local and national regulations.
Disposal methods:	For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used. If the product is in liquid form it will present the hazards detailed in this Safety Data Sheet and therefore it must be disposed of a Hazardous Waste. However cured product, that is product that has reached and gone completely solid, no longer presents a hazard and can be disposed of as non hazardous waste once the labels have been removed from the container.
Disposal of packaging:	The containers should be empty of as much product as possible. Leave the containers uncovered in a well ventilated area overnight to allow the residual product to cure. Once the product is cured it is no longer hazardous. Following the removal of the hazard labels the containers can be disposed of as non-hazardous waste.

Continued/....

14. TRANSPORT INFORMATION

ADR/RID Not classified as hazardous under transport regulations.

15. REGULATORY INFORMATION

Symbols Xn - Harmful



Risk phrases R42/43 – May cause sensitisation by inhalation and skin contact.

Safety phrases S22 – Do not breathe dust.
S23 – Do not breathe gas/fumes/vapour/spray.
S24 – Avoid contact with skin.
S37 – Wear suitable gloves.
S45 - In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
S63 – In case of accident by inhalation; remove casualty to fresh air and keep at rest.

16. OTHER INFORMATION

Text of risk phrases in section 2: R20 – Harmful by inhalation.
R36/37/38 – Irritating to eyes, respiratory system and skin.
R42/43 – May cause sensitisation by inhalation and skin contact.

Recommended restrictions: The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.

Revision: This document differs from the previous version in the following areas:
9 – colour.
9 – odour.
9 – boiling point.
9 – flash point.

SAFETY DATA SHEET

Euroflex Roofing and Joint Sealant

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

Product name: Euroflex Roofing and Joint Sealant

Description: Polyurethane sealant for joints.

Company name: Interflex Limited
Unit 7A
Crifin Enterprise Centre
Oxton Road
Epperstone
Nottinghamshire
NG14 6AT

Tel: 0115 9129 749

Fax: 0115 9129 749

Email: t.makar@ntlworld.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical characterisation: Preparation of polyurethane pre-polymer, fillers and additives.

Hazardous ingredients:

Name	CAS No.	EC No.	Conc. (%w/w)	Classification & R phrases
Aromatic Hydrocarbon C8 C10	90989-39-2	292-695-4	2.5%-10%	Xn, R37 -65
Calcium Oxide	1305-78-8		1%-2.5%	Xi, R37/38-41
Diphenylmethane-4,4'-di-isocyanate	101-68-8	202-966-0	<1%	Xn; Xi; R20-36/37/38-42/43

3. HAZARDS IDENTIFICATION

May cause acute irritation and sensitisation of the respiratory system leading to an asthmatic condition, wheeziness and tightness of the chest. Sensitised individuals may subsequently show asthmatic symptoms when exposed to very low atmospheric concentrations. Repeated exposure may lead to permanent respiratory disability. Repeated or prolonged skin contact may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis, absorption through the skin and, eventually, allergic contact dermatitis. Product splashed in the eyes may cause irritation and reversible damage.

(cont....)

Euroflex Roofing and Joint Sealant

4. FIRST AID MEASURES

Eye contact:	Wash eye thoroughly with cold water. If irritation persists, seek medical attention.
Skin contact:	Remove contamination and wash affected area thoroughly with soap and water.
Inhalation:	Move affected person away from contaminated area and into the fresh air. If breathing is irregular or stopped, give artificial respiration. If symptoms persist, seek medical advice.
Ingestion:	If confined to the mouth, do not swallow; wash out mouth with water. If swallowed, seek medical advice, showing the container/label/safety data sheet. Do not induce vomiting.
Medical treatment:	If irritation persists, seek medical attention.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:	Alcohol-resistant foam, Carbon Dioxide, powders, water spray.
Unsuitable extinguishing media:	DO NOT use water jets on fires.
Special protective equipment/ procedures:	A self-contained respirator and protective clothing should be worn. Keep containers cool with water spray until well after fire is out. Fire will produce dense black smoke. Determine the need to evacuate or isolate the area according to your local emergency plan.
Hazardous combustion products:	May produce Carbon Monoxide, Carbon Dioxide, dense black smoke, oxides of nitrogen, hydrochloric acid.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:	Avoid contact with skin and eyes. Do not breathe vapours and ventilate spillage area. Wear suitable protective equipment during spillage clean-up.
Precautions to protect the environment:	Keep away from drains and watercourses.
Methods for cleaning up:	Absorb spillage with non-combustible absorbent materials, eg. sand, earth, vermiculite. One possible decontaminate comprises: water/Ethanol or IPA/Ammonia solution (45/50/5 by volume). Scrape up into a suitable container. Seal container for disposal – see section 13.

Euroflex Roofing and Joint Sealant

7. HANDLING AND STORAGE

Advice on safe handling: Ensure good ventilation to prevent exposure levels being exceeded. Avoid eye and skin contact and breathing the vapour. Wear gloves and eye protection if necessary. Keep away from food and drink. Wash hands thoroughly with soap and water before eating or drinking. No smoking. Never use pressure to empty.

Advice on storage: Store in a cool, dry, well ventilated place between 5°C and 25°C and away from direct sunlight, heat or oxidising agent, strongly acidic, amines, alcohols and water. Keep container tightly closed and minimise exposure to atmospheric humidity and water. Carbon Dioxide will be formed which, in closed container, may cause pressurisation so take care when reopening partly used container.

Additional information: Individuals with a history of asthma allergies, chronic or recurrent respiratory disease should not be employed in any process in which this product is used.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Exposure controls for hazardous components:**

Name	CAS No.	Exposure Limits
Diphenylmethane 4,4' diisocyanate	101-68-8	HSE EH40 Maximum Exposure Limit:- 0.01 ppm (0.1 mg/m ³) for an 8 hour reference period STEL 0.02 ppm (0.2 mg/m ³)
Aromatic hydrocarbons C8 C10	90989-39-2	HSE EH40 Maximum Exposure Limit:- 50 ppm (254 mg/m ³) for an 8 hour reference period

Personal protection equipment:

Respiratory protection: Use material or forced ventilation to reduce atmospheric levels below exposure limits. Use respiratory protection if this is not possible. In well ventilated areas, air-fed respirators could be replaced by a combination of charcoal filter and particulate filter mask. Check with protective equipment manufacturers.

Skin protection: Polyvinyl gloves if prolonged skin contact likely. Barrier creams may help protect exposed areas of skin but should not be applied once exposure has occurred.

Eye protection: Safety glasses should be worn.

Hygiene measures: Exercise good industrial hygiene practice. Wash after handling especially before eating, drinking or smoking.

Additional information: Individuals with a history of asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this product is used.

Euroflex Roofing and Joint Sealant

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and odour:	Thixotropic paste, solvent.
Colour:	Black, grey and white.
Flash point:	>55°C.
Specific gravity:	1.15 – 1.19 g/cm ³ (dependent upon colour)
Solubility:	Insoluble in water but slight reaction.
Vapour tension:	<1.10 Bar at 20°C.

10. STABILITY AND REACTIVITY

Stability:	Stable at roof temperature sealed in original containers.
Conditions to avoid:	Heat sources, sources of ignition, direct sunlight.
Materials to avoid:	Keep away from oxidising agents, strongly alkaline and strongly acidic materials.
Hazardous decomposition products:	When exposed to high temperatures, may produce isocyanates, carbon monoxide and dioxide, smoke, oxides of nitrogen, chlorhydric acid, hydrogen cyanide, sulphur dioxide.

11. TOXICOLOGICAL INFORMATION

On contact with eye:	May cause smarting and irritation.
On contact with skin:	Repeated or prolonged skin contact may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis, absorption through the skin and, eventually, allergic contact dermatitis.
If inhaled:	Isocyanate components and considering toxicological data on similar preparations may cause acute irritation and sensitisation of the respiratory system leading to an asthmatic condition, wheeziness and tightness of the chest. Sensitised individuals may subsequently show asthmatic symptoms when exposed to atmospheric concentrations below the exposure limits. Repeated exposure may lead to permanent respiratory disability.
On ingestion:	May cause irritation of the mouth, throat and digestive system and eventual vomiting.
Other health hazard information:	Not known.

(cont....)

Euroflex Roofing and Joint Sealant

12. ECOLOGICAL INFORMATION

Environmental fate and distribution:	This preparation contains components which may be dangerous for the environment during pouring of the product, accidentally or voluntarily.
Ecotoxicity effects:	Product should not be allowed into drains or watercourses.
Bioaccumulation:	Unknown.
Fate and effects in waste water treatment plants:	Unknown.

13. DISPOSAL CONSIDERATIONS

Product disposal:	Product should be disposed of as Special Waste by incineration or landfill via a licensed waste disposal contractor. DO NOT empty product in drains. Residues in empty containers should be neutralised with decontaminant (see section 6).
Packaging disposal:	Product should be disposed of as Special Waste by incineration or landfill via a licensed waste disposal contractor. DO NOT empty product in drains.

14. TRANSPORT INFORMATION

Road/Rail (ADR/RID)	Not subject to ADR/RID.
Sea Transport (IMDG)	Not subject to IMDG code.
Air Transport (ICAO)	Not subject to ICAO regulations.

(cont....)

Euroflex Roofing and Joint Sealant

15. REGULATORY INFORMATION

Classification as required by The Chemicals (Hazard Information and Packaging for Supply) CHOP Regulations

Labelling according to EEC directive:

Nature of hazard: Harmful.

Hazard symbols Xn



R – phrase(s): R42 – May cause sensitisation by inhalation.

S – phrase(s): S2 – Keep out of reach of children.
S23 – Do not breathe vapours.
S24/25 – Avoid contact with skin and eyes.
S45 – In case of accident or you feel unwell, seek medical advice immediately
(show the label where possible).
S51 – Use only in well ventilated areas.

Other phrases: Contains isocyanates.
Contains Diphenylmethane – 4-4 Diisocyanate, isomers and homologues

EINICS 202-966-0

16. OTHER INFORMATION

This product Safety Data Sheet was prepared in compliance with Commission Directive 91/155/EEC, 67/548/EEC and 1999/45/EC as well as their relevant amendments, on the approximation of laws, regulations and administrative provisions relative to the classification, packaging and labelling of dangerous substances and preparations.

This product should only be used as stated in Interflex Limited literature. It is the responsibility of the persons in receipt of this Safety Data Sheet to ensure that the information contained herein is properly read and understood by all people who may use, handle, dispose or in any way come into contact with the product. If the recipient subsequently produces a formulation containing the Interflex Limited products, it is the recipients sole responsibility to ensure the transfer of all relevant information from the Interflex Limited Product Safety Data Sheet to their own Product Safety Data Sheet in compliance with Commission Directive 1999/45/EC.

All sections of this Safety Data Sheet have been amended since the previous version.

All information and instructions provided in the Safety Data Sheet (SDS) are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. Interflex Limited shall not be held responsible for any defect in the product covered by this SDS, should the existence of such defects not be detectable considering the current state of scientific and technical knowledge.

SAFETY DATA SHEET

Euroflex Series

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

Product name: Euroflex Tar and Bitumen Isolator

Company name: Interflex Limited
Unit 7A
Criftn Enterprise Centre
Oxton Road
Epperstone
Nottinghamshire
NG14 6AT

Tel: 0115 9129 749

Fax: 0115 9129 749

Email: enquiries@interflex.org.uk

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients: Isopropanol 74%
F R11 (highly flammable)

3. HAZARDS IDENTIFICATION

Main hazards: Isopropanol is a highly flammable liquid and poses a significant fire risk if not handled correctly.

Exposure to isopropanol is considered a low hazard with regards to health effects. High concentrations above the occupational exposure standard may cause irritation of the respiratory passages.

4. FIRST AID MEASURES

Inhalation: Remove casualty from source of vapours and into fresh air. If recovery is not rapid, seek medical attention.

Eye contact: Irrigate thoroughly with water for at least 10 minutes, obtain medical attention.

Ingestion: Wash out mouth with water. Do not induce vomiting.

(cont....)

Euroflex Tar and Bitumen Isolator

5. FIRE-FIGHTING MEASURES

Suitable Extinguisher: Foam, dry powder, CO₂, vaporising liquid.

Unsuitable Extinguisher: Water.

6. ACCIDENTAL RELEASE MEASURES

Remove all ignition sources. Avoid breathing vapours and contact with the skin. Keep spillages away from drains, surface and ground water and soil.

7. HANDLING AND STORAGE

Do not store or use near source of ignition. Avoid use in confined spaces and provide good ventilation.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure standard.

Isopropanol 8hr TWA 999mg/m³
15 minutes ref period 1250mg/m³

Provide good natural or general ventilation and avoid using in confined spaces.

Respiratory protection will be required in circumstances where occupational exposure standard is exceeded.

If hand contact is unavoidable use alcohol resistant gloves.

(cont....)

Euroflex Tar and Bitumen Isolator

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Colourless low viscosity liquid.
Odour:	Solvent like.
pH:	Not known.
Boiling/melting point:	Not known.
Flash point:	14°C.
Flammability:	Highly flammable.
Auto Flammability:	None.
Explosive Properties:	None.
Oxidising Properties:	None.
Density:	0.82.
Vapour Pressure:	Not known.
Solubility:	Insoluble in water and fat.
Vapour Density:	Not known.
Miscibility:	Immiscible in water.
Viscosity:	0.3-1.0.
Conductivity:	Not known.
Evaporative Rate:	Not known.

10. STABILITY AND REACTIVITY

Avoid high temperatures.

11. TOXICOLOGICAL INFORMATION

Exposure to alcohols produce moderate narcotic effects. The effects of ingestion of isopropyl alcohol is similar to other alcohols. Exposure by inhalation at the occupational exposure standard should not produce any detectable narcotic effects. It is believed that isopropyl alcohol is of low toxicity by any route.

(cont....)

SAFETY DATA SHEET

Euroflex Tar and Bitumen Isolator

12. ECOLOGICAL INFORMATION

Isopropanol is soluble in water and is volatile. No bioaccumulative potential expected.

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with European, national and local waste disposal regulations.

14. TRANSPORT INFORMATION

No special precautions envisaged in connection with the transport or carriage either within or outside the users premises.

15. REGULATORY INFORMATION

Hazard Symbols:



CHIP 3 label requirements.

F R11 (highly flammable).

S16 (keep away from sources of ignition – no smoking).

Occupational Exposure Standard.

8hr TWA – 400 ppm

15 minutes ref period – 500 ppm

Refer to Control Substances Hazardous to Health (COSHH) Regulation and HSE Guidance Notes.

This data sheet does not constitute a risk assessment as required by COSHH.

16. OTHER INFORMATION

Training: Fire precautions.

Recommended Uses and Restrictions: Barrier for roof coatings.

Further Information:

Source of Key Data: EH 40.

TECHNICAL INFORMATION

Interflex One Component Coatings and Adhesives

SAFE USE AND WASTE DISPOSAL

The following guidelines refer to Euroflex series.

SAFE USE AND TRANSPORT

Interflex's one pack coatings and adhesives are all urethane formulations based on MDI. MDI is commonly known as diphenylmethane-diisocyanate and has a very low vapour pressure (<0.00001 mbar – which is a hundred million times less than atmospheric pressure) This low volatility is such that the MEL (maximum exposure limit) of 0.02 mg/m³ is unlikely to be reached under normal use. This would apply to the normal pure MDI but, in fact, the materials supplied contain less than 1% MDI.

Anyone with breathing difficulties (such as asthmatics), should avoid using this type of product.

MDI is not classed as hazardous for transportation purposes and therefore has no UN NO. No tremcard is required.

DISPOSAL

Once The products have cured they present no hazard.

Containers should be left open to cure (24 hours). After this time the containers can be disposed of as normal waste.

HEALTH AND SAFETY

Please consult the individual product Health and Safety Datasheet for further information.